

2 Flutes HARDMAX



Size  $\phi 0.2 \sim \phi 6$

# HLRS2000/HLRS2000E



Material Applications (★ Highly Recommended ● Recommended ○ Suggested)

Work Material																	
Carbon Steels S45C S55C	Alloy Steels SK / SCM SUS	Prehardened Steels NAK HPM	Hardened Steels					Cast Iron	Aluminum Alloys	Graphite	Copper	Plastics	Glass Filled Plastics	Titanium Alloys	Heat Resistant Alloys	Cemented Carbide	Hard Brittle (Non-Metallic) Materials
			~50HRC	~55HRC	~60HRC	~65HRC	~70HRC										
○	○	●	●	●	●	○	○			●				○	○		

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Total 353 models


Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥				
HLRS 2002-005-005E	○	0.2	RO.05	0.5	0.2	0.17	16°	50	4	12,320				
HLRS 2002-005-010E	○			1				50	4	12,320				
HLRS 2002-005-015E	○			1.5				50	4	12,320				
HLRS 2002-005-020E	○			2				50	4	12,320				
HLRS 2003-005-010E	○	0.3	RO.05	1	0.3	0.27	16°	50	4	11,870				
HLRS 2003-005-015E	○			1.5				50	4	11,870				
HLRS 2003-005-020E	○			2				50	4	11,870				
HLRS 2003-005-025E	○			2.5				50	4	13,200				
HLRS 2003-005-030E	○			3				50	4	13,200				
HLRS 2004-005-010E	○	0.4	RO.05	1	0.4	0.38	16°	50	4	7,910				
HLRS 2004-005-015E	○			1.5				50	4	7,910				
HLRS 2004-005-020E	○			2				50	4	7,910				
HLRS 2004-005-030E	○			3				50	4	7,910				
HLRS 2004-005-040E	○			4				50	4	7,910				
HLRS 2004-01-010				RO.1				1				50	4	7,910
HLRS 2004-01-015								1.5	50	4	7,910			
HLRS 2004-01-020								2	50	4	7,910			
HLRS 2004-01-030								3	50	4	7,910			
HLRS 2004-01-040								4	50	4	7,910			
HLRS 2005-005-010		0.5	RO.05	1	0.5	0.48	16°	50	4	6,440				
HLRS 2005-005-020				2				50	4	6,440				
HLRS 2005-005-030				3				50	4	6,440				
HLRS 2005-005-040				4				50	4	6,440				
HLRS 2005-005-050				5				50	4	6,440				
HLRS 2005-01-010				RO.1				1				50	4	6,440
HLRS 2005-01-020								2	50	4	6,440			
HLRS 2005-01-030								3	50	4	6,440			
HLRS 2005-01-040								4	50	4	6,440			
HLRS 2005-01-050								5	50	4	6,440			
HLRS 2005-01-060								6				50	4	6,440


Next Page →

**Features**

**Long Neck Radius design for high efficiency and high quality milling.  
Recommended for various applications from Copper and Raw Materials to Hard Materials.  
Both dry and wet coolant offer stable and long tool life.  
Refer to page 358 for 4 flute HLRS.**



The shank taper angle shown is not an exact value and to avoid contact with the work piece, we recommend the user controls the precise value of this angle. Shank taper angle should not make contact with the work piece.



	Diameter Tolerance	Corner Radius Tolerance
Standard Tolerance Type	0/-0.015	Nominal Radius $\pm 0.005$
Excellent Tolerance Type	0/-0.01	Nominal Radius $\pm 0.005$

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_1$	Effective Length by Inclined Angles						
					30'	1°	1°30'	2°	3°		
HLRS 2002-005-005E	○	0.2	R0.05	0.5	0.67	0.71	0.75	0.78	0.85		
HLRS 2002-005-010E	○			1	1.20	1.26	1.31	1.36	1.45		
HLRS 2002-005-015E	○			1.5	1.72	1.80	1.87	1.92	2.03		
HLRS 2002-005-020E	○			2	2.25	2.34	2.41	2.48	2.59		
HLRS 2003-005-010E	○	0.3	R0.05	1	1.24	1.31	1.38	1.44	1.55		
HLRS 2003-005-015E	○			1.5	1.72	1.83	1.91	1.99	2.12		
HLRS 2003-005-020E	○			2	2.26	2.37	2.47	2.55	2.70		
HLRS 2003-005-025E	○			2.5	2.78	2.91	3.02	3.11	3.27		
HLRS 2003-005-030E	○	0.4	R0.05	3	3.31	3.45	3.57	3.66	3.83		
HLRS 2004-005-010E	○			1	1.31	1.40	1.49	1.57	1.72		
HLRS 2004-005-015E	○			1.5	1.79	1.92	2.03	2.13	2.31		
HLRS 2004-005-020E	○			2	2.33	2.48	2.60	2.71	2.90		
HLRS 2004-005-030E	○	0.4	R0.05	3	3.40	3.58	3.72	3.85	4.07		
HLRS 2004-005-040E	○			4	4.45	4.66	4.82	4.97	5.21		
HLRS 2004-01-010				0.1	R0.1	1	1.28	1.38	1.46	1.55	1.69
HLRS 2004-01-015						1.5	1.76	1.90	2.01	2.11	2.28
HLRS 2004-01-020		2	2.30			2.46	2.58	2.69	2.89		
HLRS 2004-01-030		3	3.38			3.56	3.71	3.83	4.06		
HLRS 2004-01-040		0.5	R0.05	4	4.44	4.64	4.81	4.95	5.20		
HLRS 2005-005-010				1	1.34	1.46	1.57	1.67	1.86		
HLRS 2005-005-020				2	2.37	2.55	2.71	2.84	3.08		
HLRS 2005-005-030				3	3.45	3.67	3.85	4.00	4.27		
HLRS 2005-005-040		0.5	R0.05	4	4.52	4.77	4.97	5.14	5.44		
HLRS 2005-005-050				5	5.58	5.85	6.07	6.26	6.58		
HLRS 2005-01-010				0.1	R0.1	1	1.34	1.45	1.56	1.66	1.85
HLRS 2005-01-020						2	2.37	2.55	2.70	2.83	3.07
HLRS 2005-01-030		3	3.45			3.67	3.84	4.00	4.26		
HLRS 2005-01-040		4	4.52			4.76	4.96	5.13	5.43		
HLRS 2005-01-050		0.5	R0.1	5	5.58	5.85	6.07	6.25	6.57		
HLRS 2005-01-060				6	6.63	6.93	7.16	7.36	7.70		

Next Page →

- 3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

## 2 Flutes HARDMAX


Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥				
HLRS 2006-005-020		0.6	RO.05	2	0.6	0.58	16°	50	4	6,440				
HLRS 2006-005-030				3				50	4	6,440				
HLRS 2006-005-040				4				50	4	6,440				
HLRS 2006-005-060				6				50	4	6,440				
HLRS 2006-005-080				8				50	4	6,440				
HLRS 2006-01-020				2				RO.1	2	50	4	6,440		
HLRS 2006-01-020E	○		2	50					4	7,080				
HLRS 2006-01-030			3	50					4	6,440				
HLRS 2006-01-030E	○		3	50					4	7,080				
HLRS 2006-01-040			4	50					4	6,440				
HLRS 2006-01-040E	○		4	50					4	7,080				
HLRS 2006-01-060			6	50					4	6,440				
HLRS 2006-01-080			8	50					4	6,440				
HLRS 2006-02-020			RO.2	2					50	4	6,440			
HLRS 2006-02-030				3					50	4	6,440			
HLRS 2006-02-040				4				50	4	6,440				
HLRS 2006-02-060		6		50	4	6,440								
HLRS 2006-02-080		8		50	4	6,440								
HLRS 2007-01-040		0.7		RO.1	4	0.7	0.68	16°	50	4	6,780			
HLRS 2007-01-060					6				50	4	6,780			
HLRS 2007-02-040				RO.2	4				50	4	6,780			
HLRS 2007-02-060			6		50				4	6,780				
HLRS 2008-005-040		0.8	RO.05	4	0.8	0.78	16°	50	4	7,340				
HLRS 2008-005-060				6				50	4	7,340				
HLRS 2008-005-080				8				50	4	7,340				
HLRS 2008-01-040			RO.1	4				50	4	7,340				
HLRS 2008-01-060				6				50	4	7,340				
HLRS 2008-01-080				8				50	4	7,340				
HLRS 2008-02-040				RO.2				4	50	4	7,340			
HLRS 2008-02-060								6	50	4	7,340			
HLRS 2008-02-080								8	50	4	7,340			
HLRS 2010-005-020			1	RO.05				2	1	0.95	16°	50	4	6,240
HLRS 2010-005-030								3				50	4	6,240
HLRS 2010-005-040								4				50	4	6,240
HLRS 2010-005-050		5			50	4	6,240							
HLRS 2010-005-060		6			50	4	6,780							
HLRS 2010-005-080		8			50	4	6,780							
HLRS 2010-005-100		10			50	4	6,780							
HLRS 2010-005-120		12			55	4	6,780							
HLRS 2010-005-160		16			60	4	8,990							
HLRS 2010-005-200		20			60	4	9,980							
HLRS 2010-01-020		RO.1		2	50	4	6,240							
HLRS 2010-01-020E	○			2	50	4	6,860							
HLRS 2010-01-030				3	50	4	6,240							
HLRS 2010-01-040				4	50	4	6,240							
HLRS 2010-01-040E	○			4	50	4	6,860							
HLRS 2010-01-050				5	50	4	6,240							
HLRS 2010-01-060				6	50	4	6,780							
HLRS 2010-01-060E	○			6	50	4	7,460							

- φ3mm Shark V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_1$	Effective Length by Inclined Angles					
					30'	1°	1°30'	2°	3°	
HLRS 2006-005-020		0.6	RO.05	2	2.38	2.61	2.79	2.95	3.22	
HLRS 2006-005-030				3	3.48	3.74	3.95	4.13	4.30	
HLRS 2006-005-040				4	4.56	4.85	5.08	5.28	5.67	
HLRS 2006-005-060				6	6.68	7.03	7.30	7.55	8.12	
HLRS 2006-005-080				8	8.79	9.18	9.50	9.83	10.56	
HLRS 2006-01-020			RO.1	2	2.37	2.60	2.78	2.93	3.20	
HLRS 2006-01-020E	○			2	2.37	2.60	2.78	2.93	3.20	
HLRS 2006-01-030				3	3.47	3.73	3.94	4.11	4.28	
HLRS 2006-01-030E	○			3	3.47	3.73	3.94	4.11	4.28	
HLRS 2006-01-040				4	4.55	4.84	5.07	5.26	5.65	
HLRS 2006-01-040E	○			4	4.55	4.84	5.07	5.26	5.65	
HLRS 2006-01-060				6	6.68	7.03	7.30	7.54	8.10	
HLRS 2006-01-080				8	8.79	9.18	9.50	9.82	10.55	
HLRS 2006-02-020				RO.2	2	2.34	2.56	2.74	2.90	3.18
HLRS 2006-02-030					3	3.44	3.70	3.91	4.09	4.41
HLRS 2006-02-040			4		4.53	4.82	5.05	5.23	5.61	
HLRS 2006-02-060		6	6.66		7.01	7.28	7.51	8.06		
HLRS 2006-02-080		8	8.79	9.17	9.48	9.81	10.53			
HLRS 2007-01-040		0.7	RO.1	4	4.55	4.84	5.07	5.26	5.65	
HLRS 2007-01-060				6	6.68	7.03	7.30	7.54	8.10	
HLRS 2007-02-040			RO.2	4	4.53	4.82	5.05	5.23	5.61	
HLRS 2007-02-060				6	6.66	7.01	7.28	7.51	8.06	
HLRS 2008-005-040		0.8	RO.05	4	4.56	4.85	5.08	5.28	5.67	
HLRS 2008-005-060				6	6.68	7.03	7.30	7.55	8.12	
HLRS 2008-005-080				8	8.79	9.18	9.50	9.83	10.56	
HLRS 2008-01-040			RO.1	4	4.55	4.84	5.07	5.26	5.65	
HLRS 2008-01-060				6	6.68	7.03	7.30	7.54	8.10	
HLRS 2008-01-080				8	8.79	9.18	9.50	9.82	10.55	
HLRS 2008-02-040			RO.2	4	4.53	4.82	5.05	5.23	5.61	
HLRS 2008-02-060				6	6.66	7.01	7.28	7.51	8.06	
HLRS 2008-02-080				8	8.79	9.17	9.48	9.81	10.53	
HLRS 2010-005-020			1	RO.05	2	2.51	2.86	2.70	3.01	3.28
HLRS 2010-005-030					3	3.59	3.82	4.01	4.18	4.51
HLRS 2010-005-040					4	4.72	4.92	5.14	5.33	5.73
HLRS 2010-005-050		5			5.72	6.01	6.25	6.47	6.95	
HLRS 2010-005-060		6			6.77	7.09	7.35	7.61	8.18	
HLRS 2010-005-080		8			8.87	9.24	9.55	9.88	10.62	
HLRS 2010-005-100		10			10.97	11.37	11.75	12.16	13.07	
HLRS 2010-005-120		12			13.05	13.50	13.96	14.44	15.52	
HLRS 2010-005-160		16			17.20	17.76	18.36	18.99	20.41	
HLRS 2010-005-200		20			21.33	22.02	22.76	23.55	25.31	
HLRS 2010-01-020		RO.1		2	2.53	2.71	2.88	3.01	3.27	
HLRS 2010-01-020E	○			2	2.53	2.71	2.88	3.01	3.27	
HLRS 2010-01-030				3	3.58	3.81	4.00	4.18	4.49	
HLRS 2010-01-040				4	4.67	4.93	5.14	5.33	5.72	
HLRS 2010-01-040E	○			4	4.67	4.93	5.14	5.33	5.72	
HLRS 2010-01-050				5	5.71	6.00	6.24	6.46	6.94	
HLRS 2010-01-060				6	6.78	7.10	7.36	7.60	8.17	
HLRS 2010-01-060E	○			6	6.78	7.10	7.36	7.60	8.17	



Next Page →

## 2 Flutes HARDMAX


Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥	
HLRS 2010-01-080		1	RO.1	8	1	0.95	16°	50	4	6,780	
HLRS 2010-01-100				10				50	4	6,780	
HLRS 2010-01-120				12				55	4	6,780	
HLRS 2010-01-160				16				60	4	8,990	
HLRS 2010-01-200				20				60	4	9,980	
HLRS 2010-02-020			RO.2	2				50	4	6,240	
HLRS 2010-02-020E	○			2				50	4	6,860	
HLRS 2010-02-030				3				50	4	6,240	
HLRS 2010-02-040				4				50	4	6,240	
HLRS 2010-02-040E	○			4				50	4	6,860	
HLRS 2010-02-050				5				50	4	6,240	
HLRS 2010-02-060				6				50	4	6,780	
HLRS 2010-02-060E	○			6				50	4	7,460	
HLRS 2010-02-080				8				50	4	6,780	
HLRS 2010-02-100				10				50	4	6,780	
HLRS 2010-02-120				12				55	4	6,780	
HLRS 2010-02-160				16				60	4	8,990	
HLRS 2010-02-200				20				60	4	9,980	
HLRS 2010-03-020				RO.3				2	50	4	6,240
HLRS 2010-03-020E	○							2	50	4	6,860
HLRS 2010-03-030		3	50		4	6,240					
HLRS 2010-03-040		4	50		4	6,240					
HLRS 2010-03-040E	○	4	50		4	6,860					
HLRS 2010-03-050		5	50		4	6,240					
HLRS 2010-03-060		6	50		4	6,780					
HLRS 2010-03-060E	○	6	50		4	7,460					
HLRS 2010-03-080		8	50		4	6,780					
HLRS 2010-03-100		10	50		4	6,780					
HLRS 2010-03-120		12	55	4	6,780						
HLRS 2010-03-160		16	60	4	8,990						
HLRS 2010-03-200		20	60	4	9,980						
HLRS 2012-02-060		1.2	RO.2	6	1.2	1.14	16°	50	4	7,000	
HLRS 2012-02-120				12				55	4	7,000	
HLRS 2012-02-200			20	60				4	10,620		
HLRS 2012-03-060			RO.3	6				50	4	7,000	
HLRS 2012-03-120				12				55	4	7,000	
HLRS 2012-03-200		20		60	4	10,620					
HLRS 2015-005-040		1.5	RO.05	4	1.5	1.45	16°	50	4	6,650	
HLRS 2015-005-060				6				50	4	6,650	
HLRS 2015-005-080				8				50	4	7,000	
HLRS 2015-005-100				10				50	4	7,000	
HLRS 2015-01-040				RO.1				4	50	4	6,650
HLRS 2015-01-060			6					50	4	6,650	
HLRS 2015-01-080			8					50	4	7,000	
HLRS 2015-01-100			10					50	4	7,000	
HLRS 2015-01-120			12					55	4	7,000	
HLRS 2015-01-160			16	55				4	7,000		
HLRS 2015-01-200		20	60	4	7,000						

- φ3mm Shark V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_e$	Effective Length by Inclined Angles					
					30'	1°	1°30'	2°	3°	
HLRS 2010-01-080		1	RO.1	8	8.88	9.24	9.56	9.88	10.61	
HLRS 2010-01-100				10	10.97	11.37	11.76	12.16	13.06	
HLRS 2010-01-120				12	13.05	13.50	13.96	14.44	15.51	
HLRS 2010-01-160				16	17.20	17.76	18.36	18.99	20.40	
HLRS 2010-01-200				20	21.33	22.02	22.76	23.54	25.30	
HLRS 2010-02-020			RO.2	2	2.51	2.69	2.86	2.98	3.23	
HLRS 2010-02-020E	○			2	2.51	2.69	2.86	2.98	3.23	
HLRS 2010-02-030				3	3.58	3.80	3.99	4.16	4.47	
HLRS 2010-02-040				4	4.65	4.91	5.12	5.30	5.68	
HLRS 2010-02-040E	○			4	4.65	4.91	5.12	5.30	5.68	
HLRS 2010-02-050				5	5.71	6.00	6.23	6.45	6.92	
HLRS 2010-02-060				6	6.76	7.08	7.34	7.57	8.13	
HLRS 2010-02-060E	○			6	6.76	7.08	7.34	7.57	8.13	
HLRS 2010-02-080				8	8.86	9.22	9.54	9.85	10.57	
HLRS 2010-02-100				10	10.95	11.35	11.74	12.13	13.02	
HLRS 2010-02-120				12	13.03	13.48	13.94	14.41	15.47	
HLRS 2010-02-160				16	17.18	17.74	18.34	18.96	20.36	
HLRS 2010-02-200				20	21.31	22.00	22.74	23.51	25.26	
HLRS 2010-03-020				RO.3	2	2.49	2.67	2.84	2.95	3.19
HLRS 2010-03-020E	○				2	2.49	2.67	2.84	2.95	3.19
HLRS 2010-03-030			3		3.57	3.79	3.98	4.14	4.45	
HLRS 2010-03-040			4		4.63	4.89	5.10	5.27	5.64	
HLRS 2010-03-040E	○		4		4.63	4.89	5.10	5.27	5.64	
HLRS 2010-03-050			5		5.70	5.99	6.22	6.43	6.90	
HLRS 2010-03-060			6		6.74	7.06	7.32	7.54	8.09	
HLRS 2010-03-060E	○		6		6.74	7.06	7.32	7.54	8.09	
HLRS 2010-03-080			8		8.84	9.20	9.52	9.82	10.53	
HLRS 2010-03-100			10		10.93	11.33	11.72	12.10	12.98	
HLRS 2010-03-120			12		13.01	13.46	13.92	14.38	15.43	
HLRS 2010-03-160			16		17.16	17.72	18.32	18.93	20.32	
HLRS 2010-03-200		20	21.29		21.98	22.72	23.48	25.22		
HLRS 2012-02-060		1.2	RO.2		6	6.18	6.38	6.59	6.82	7.33
HLRS 2012-02-120					12	12.37	12.77	13.19	13.65	14.67
HLRS 2012-02-200				20	20.62	21.29	22.00	22.76	24.46	
HLRS 2012-03-060			RO.3	6	6.18	6.38	6.59	6.81	7.31	
HLRS 2012-03-120				12	12.37	12.77	13.19	13.64	14.66	
HLRS 2012-03-200				20	20.62	21.28	21.99	22.75	24.45	
HLRS 2015-005-040		1.5	RO.05	4	4.12	4.26	4.40	4.55	4.89	
HLRS 2015-005-060				6	6.18	6.39	6.60	6.83	7.34	
HLRS 2015-005-080				8	8.25	8.52	8.80	9.11	9.79	
HLRS 2015-005-100				10	10.31	10.64	11.00	11.38	12.24	
HLRS 2015-01-040			RO.1	4	4.12	4.25	4.40	4.55	4.89	
HLRS 2015-01-060				6	6.18	6.38	6.60	6.83	7.34	
HLRS 2015-01-080				8	8.24	8.51	8.80	9.10	9.78	
HLRS 2015-01-100				10	10.31	10.64	11.00	11.38	12.23	
HLRS 2015-01-120				12	12.37	12.77	13.20	13.66	14.68	
HLRS 2015-01-160				16	16.50	17.03	17.60	18.21	19.57	
HLRS 2015-01-200				20	20.62	21.29	22.00	22.77	No Interference	



Next Page →

## 2 Flutes HARDMAX

Unit (mm)


Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_e$	Length of Cut $\ell$	Neck Diameter $\phi d_i$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥
HLRS 2015-02-040		1.5	RO.2	4	1.5	1.45	16°	50	4	6,650
HLRS 2015-02-060				6				50	4	6,650
HLRS 2015-02-080				8				50	4	7,000
HLRS 2015-02-100				10				50	4	7,000
HLRS 2015-02-120				12				55	4	7,000
HLRS 2015-02-160				16				55	4	7,000
HLRS 2015-02-200				20				60	4	7,000
HLRS 2015-03-040				RO.3				4	50	4
HLRS 2015-03-060			6					50	4	6,650
HLRS 2015-03-080			8					50	4	7,000
HLRS 2015-03-100			10					50	4	7,000
HLRS 2015-03-120			12					55	4	7,000
HLRS 2015-03-160			16					55	4	7,000
HLRS 2015-03-200			20					60	4	7,000
HLRS 2015-05-040			RO.5					4	50	4
HLRS 2015-05-060				6				50	4	6,650
HLRS 2015-05-080				8				50	4	7,000
HLRS 2015-05-100				10				50	4	7,000
HLRS 2015-05-120				12				55	4	7,000
HLRS 2015-05-160				16				55	4	7,000
HLRS 2015-05-200		20		60	4	7,000				
HLRS 2020-005-040		2		RO.05	4	2	1.92	16°	50	4
HLRS 2020-005-060			6		50				4	6,650
HLRS 2020-005-080			8		50				4	7,000
HLRS 2020-005-100			10		50				4	7,000
HLRS 2020-01-040			RO.1		4				50	4
HLRS 2020-01-040E	○			4	50				4	7,320
HLRS 2020-01-060				6	50				4	6,650
HLRS 2020-01-060E	○			6	50				4	7,320
HLRS 2020-01-080				8	50				4	7,000
HLRS 2020-01-080E	○			8	50				4	7,700
HLRS 2020-01-100				10	50				4	7,000
HLRS 2020-01-100E	○			10	50				4	7,700
HLRS 2020-01-120				12	55				4	7,000
HLRS 2020-01-120E	○			12	55				4	7,700
HLRS 2020-01-160				16	60				4	7,000
HLRS 2020-01-200				20	60				4	7,000
HLRS 2020-01-260				26	70				4	7,000
HLRS 2020-01-300				30	70				4	7,000
HLRS 2020-02-040				RO.2	4				50	4
HLRS 2020-02-040E	○		4		50				4	7,320
HLRS 2020-02-060		6	50		4	6,650				
HLRS 2020-02-060E	○	6	50		4	7,320				
HLRS 2020-02-080		8	50		4	7,000				
HLRS 2020-02-080E	○	8	50		4	7,700				
HLRS 2020-02-100		10	50		4	7,000				
HLRS 2020-02-100E	○	10	50		4	7,700				

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data



Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_e$	Effective Length by Inclined Angles					
					30'	1°	1°30'	2°	3°	
HLRS 2015-02-040		1.5	RO.2	4	4.12	4.25	4.39	4.54	4.88	
HLRS 2015-02-060				6	6.18	6.38	6.59	6.82	7.33	
HLRS 2015-02-080				8	8.24	8.51	8.79	9.10	9.77	
HLRS 2015-02-100				10	10.31	10.64	10.99	11.37	12.22	
HLRS 2015-02-120				12	12.37	12.77	13.19	13.65	14.67	
HLRS 2015-02-160				16	16.49	17.03	17.60	18.21	19.56	
HLRS 2015-02-200				20	20.62	21.29	22.00	22.76	No Interference	
HLRS 2015-03-040			RO.3	4	4.12	4.25	4.39	4.54	4.87	
HLRS 2015-03-060				6	6.18	6.38	6.59	6.81	7.31	
HLRS 2015-03-080				8	8.24	8.51	8.79	9.09	9.76	
HLRS 2015-03-100				10	10.30	10.64	10.99	11.37	12.21	
HLRS 2015-03-120				12	12.37	12.77	13.19	13.64	14.66	
HLRS 2015-03-160				16	16.49	17.02	17.59	18.20	19.55	
HLRS 2015-03-200				20	20.62	21.28	21.99	22.75	No Interference	
HLRS 2015-05-040			RO.5	4	4.11	4.24	4.38	4.52	4.85	
HLRS 2015-05-060				6	6.18	6.37	6.58	6.80	7.29	
HLRS 2015-05-080				8	8.24	8.50	8.78	9.08	9.74	
HLRS 2015-05-100				10	10.30	10.63	10.98	11.35	12.19	
HLRS 2015-05-120				12	12.36	12.76	13.18	13.63	14.64	
HLRS 2015-05-160				16	16.49	17.02	17.58	18.19	19.53	
HLRS 2015-05-200		20		20.62	21.28	21.98	22.74	24.42		
HLRS 2020-005-040		2	RO.05	4	4.16	4.29	4.44	4.59	4.94	
HLRS 2020-005-060				6	6.22	6.42	6.64	6.87	7.38	
HLRS 2020-005-080				8	8.28	8.55	8.84	9.15	9.83	
HLRS 2020-005-100				10	10.35	10.68	11.04	11.42	12.28	
HLRS 2020-01-040			RO.1	4	4.16	4.29	4.43	4.59	4.93	
HLRS 2020-01-040E	○			4	4.16	4.29	4.43	4.59	4.93	
HLRS 2020-01-060				6	6.22	6.42	6.64	6.87	7.38	
HLRS 2020-01-060E	○			6	6.22	6.42	6.64	6.87	7.38	
HLRS 2020-01-080				8	8.28	8.55	8.84	9.14	9.83	
HLRS 2020-01-080E	○			8	8.28	8.55	8.84	9.14	9.83	
HLRS 2020-01-100				10	10.34	10.68	11.04	11.42	12.27	
HLRS 2020-01-100E	○			10	10.34	10.68	11.04	11.42	12.27	
HLRS 2020-01-120				12	12.41	12.81	13.24	13.70	14.72	
HLRS 2020-01-120E	○			12	12.41	12.81	13.24	13.70	14.72	
HLRS 2020-01-160				16	16.53	17.07	17.64	18.25	No Interference	
HLRS 2020-01-200				20	20.66	21.33	22.04	22.81	No Interference	
HLRS 2020-01-260				26	26.85	27.72	28.65	No Interference	No Interference	
HLRS 2020-01-300				30	30.97	31.98	33.05	No Interference	No Interference	
HLRS 2020-02-040				RO.2	4	4.15	4.29	4.43	4.58	4.92
HLRS 2020-02-040E	○				4	4.15	4.29	4.43	4.58	4.92
HLRS 2020-02-060		6	6.22		6.42	6.63	6.86	7.37		
HLRS 2020-02-060E	○	6	6.22		6.42	6.63	6.86	7.37		
HLRS 2020-02-080		8	8.28		8.55	8.83	9.14	9.82		
HLRS 2020-02-080E	○	8	8.28		8.55	8.83	9.14	9.82		
HLRS 2020-02-100		10	10.34		10.68	11.03	11.41	12.26		
HLRS 2020-02-100E	○	10	10.34		10.68	11.03	11.41	12.26		




Next Page ➔



## 2 Flutes HARDMAX

Unit (mm)




Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥
HLRS 2020-02-120		2	RO.2	12	2	1.92	16°	55	4	7,000
HLRS 2020-02-120E	○			12				55	4	7,700
HLRS 2020-02-160				16				60	4	7,000
HLRS 2020-02-200				20				60	4	7,000
HLRS 2020-02-260				26				70	4	7,000
HLRS 2020-02-300				30				70	4	7,000
HLRS 2020-03-040			RO.3	4				50	4	6,650
HLRS 2020-03-040E	○			4				50	4	7,320
HLRS 2020-03-060				6				50	4	6,650
HLRS 2020-03-060E	○			6				50	4	7,320
HLRS 2020-03-080				8				50	4	7,000
HLRS 2020-03-080E	○			8				50	4	7,700
HLRS 2020-03-100				10				50	4	7,000
HLRS 2020-03-100E	○			10				50	4	7,700
HLRS 2020-03-120				12				55	4	7,000
HLRS 2020-03-120E	○			12				55	4	7,700
HLRS 2020-03-160				16				60	4	7,000
HLRS 2020-03-200				20				60	4	7,000
HLRS 2020-03-260				26				70	4	7,000
HLRS 2020-03-300				30				70	4	7,000
HLRS 2020-05-040			RO.5	4				50	4	6,650
HLRS 2020-05-040E	○			4				50	4	7,320
HLRS 2020-05-060				6				50	4	6,650
HLRS 2020-05-060E	○			6				50	4	7,320
HLRS 2020-05-080				8				50	4	7,000
HLRS 2020-05-080E	○			8				50	4	7,700
HLRS 2020-05-100				10				50	4	7,000
HLRS 2020-05-100E	○			10				50	4	7,700
HLRS 2020-05-120				12				55	4	7,000
HLRS 2020-05-120E	○			12				55	4	7,700
HLRS 2020-05-160		16		60	4	7,000				
HLRS 2020-05-200		20		60	4	7,000				
HLRS 2020-05-260		26		70	4	7,000				
HLRS 2020-05-300		30		70	4	7,000				
HLRS 2025-01-100		2.5	RO.1	10	2.5	2.42	16°	50	4	7,340
HLRS 2025-01-200				20				60	4	7,570
HLRS 2025-01-300				30				70	4	7,800
HLRS 2025-02-100			RO.2	10				50	4	7,340
HLRS 2025-02-200				20				60	4	7,570
HLRS 2025-02-300				30				70	4	7,800
HLRS 2025-03-100			RO.3	10				50	4	7,340
HLRS 2025-03-200				20				60	4	7,570
HLRS 2025-03-300				30				70	4	7,800
HLRS 2025-05-100			RO.5	10				50	4	7,340
HLRS 2025-05-200				20				60	4	7,570
HLRS 2025-05-300				30				70	4	7,800

Next Page →

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_e$	Effective Length by Inclined Angles				
					30°	1°	1°30'	2°	3°
HLRS 2020-02-120		2	R0.2	12	12.40	12.81	13.23	13.69	14.71
HLRS 2020-02-120E	○			12	12.40	12.81	13.23	13.69	14.71
HLRS 2020-02-160				16	16.53	17.06	17.64	18.25	No Interference
HLRS 2020-02-200				20	20.66	21.32	22.04	22.80	No Interference
HLRS 2020-02-260				26	26.84	27.71	28.64	No Interference	No Interference
HLRS 2020-02-300				30	30.97	31.97	33.04	No Interference	No Interference
HLRS 2020-03-040			R0.3	4	4.15	4.28	4.42	4.57	4.91
HLRS 2020-03-040E	○			4	4.15	4.28	4.42	4.57	4.91
HLRS 2020-03-060				6	6.21	6.41	6.63	6.85	7.36
HLRS 2020-03-060E	○			6	6.21	6.41	6.63	6.85	7.36
HLRS 2020-03-080				8	8.28	8.54	8.83	9.13	9.80
HLRS 2020-03-080E	○			8	8.28	8.54	8.83	9.13	9.80
HLRS 2020-03-100				10	10.34	10.67	11.03	11.41	12.25
HLRS 2020-03-100E	○			10	10.34	10.67	11.03	11.41	12.25
HLRS 2020-03-120				12	12.40	12.80	13.23	13.68	14.70
HLRS 2020-03-120E	○			12	12.40	12.80	13.23	13.68	14.70
HLRS 2020-03-160				16	16.53	17.06	17.63	18.24	19.59
HLRS 2020-03-200				20	20.65	21.32	22.03	22.79	No Interference
HLRS 2020-03-260				26	26.84	27.71	28.64	No Interference	No Interference
HLRS 2020-03-300				30	30.97	31.97	33.04	No Interference	No Interference
HLRS 2020-05-040			R0.5	4	4.15	4.28	4.41	4.56	4.89
HLRS 2020-05-040E	○			4	4.15	4.28	4.41	4.56	4.89
HLRS 2020-05-060				6	6.21	6.41	6.62	6.84	7.34
HLRS 2020-05-060E	○			6	6.21	6.41	6.62	6.84	7.34
HLRS 2020-05-080				8	8.27	8.54	8.82	9.12	9.78
HLRS 2020-05-080E	○			8	8.27	8.54	8.82	9.12	9.78
HLRS 2020-05-100				10	10.34	10.67	11.02	11.39	12.23
HLRS 2020-05-100E	○			10	10.34	10.67	11.02	11.39	12.23
HLRS 2020-05-120				12	12.40	12.80	13.22	13.67	14.68
HLRS 2020-05-120E	○			12	12.40	12.80	13.22	13.67	14.68
HLRS 2020-05-160		16		16.53	17.06	17.62	18.23	19.57	
HLRS 2020-05-200		20		20.65	21.31	22.02	22.78	No Interference	
HLRS 2020-05-260		26		26.84	27.70	28.63	No Interference	No Interference	
HLRS 2020-05-300		30		30.97	31.96	33.03	No Interference	No Interference	
HLRS 2025-01-100		2.5	R0.1	10	10.34	10.68	11.04	11.42	12.27
HLRS 2025-01-200				20	20.66	21.33	22.04	No Interference	No Interference
HLRS 2025-01-300				30	30.97	31.98	No Interference	No Interference	No Interference
HLRS 2025-02-100			R0.2	10	10.34	10.68	11.03	11.41	12.26
HLRS 2025-02-200				20	20.66	21.32	22.04	No Interference	No Interference
HLRS 2025-02-300				30	30.97	31.97	No Interference	No Interference	No Interference
HLRS 2025-03-100			R0.3	10	10.34	10.67	11.03	11.41	12.25
HLRS 2025-03-200				20	20.65	21.32	22.03	No Interference	No Interference
HLRS 2025-03-300				30	30.97	31.97	No Interference	No Interference	No Interference
HLRS 2025-05-100			R0.5	10	10.34	10.67	11.02	11.39	12.23
HLRS 2025-05-200				20	20.65	21.31	22.02	No Interference	No Interference
HLRS 2025-05-300				30	30.97	31.96	No Interference	No Interference	No Interference



Next Page ➡

## 2 Flutes HARDMAX

Unit (mm)


Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥	
HLRS 2030-01-060		3	RO.1	6	3	2.92	16°	55	6	6,000	
HLRS 2030-01-060E	○			6				55	6	6,600	
HLRS 2030-01-120				12				55	6	7,800	
HLRS 2030-01-160				16				60	6	9,100	
HLRS 2030-01-160E	○			16				60	6	10,010	
HLRS 2030-01-180				18				60	6	9,100	
HLRS 2030-01-200				20				60	6	9,100	
HLRS 2030-01-260				26				70	6	9,100	
HLRS 2030-01-300				30				70	6	9,100	
HLRS 2030-01-360				36				80	6	11,200	
HLRS 2030-02-060				RO.2				6	55	6	6,000
HLRS 2030-02-060E	○							6	55	6	6,600
HLRS 2030-02-120			12					55	6	7,800	
HLRS 2030-02-160			16					60	6	9,100	
HLRS 2030-02-160E	○		16					60	6	10,010	
HLRS 2030-02-180			18					60	6	9,100	
HLRS 2030-02-200			20					60	6	9,100	
HLRS 2030-02-260			26					70	6	9,100	
HLRS 2030-02-300			30					70	6	9,100	
HLRS 2030-02-360			36					80	6	11,200	
HLRS 2030-03-060			RO.3					6	55	6	6,000
HLRS 2030-03-060E	○							6	55	6	6,600
HLRS 2030-03-120				12				55	6	7,800	
HLRS 2030-03-160				16				60	6	9,100	
HLRS 2030-03-160E	○			16				60	6	10,010	
HLRS 2030-03-180				18				60	6	9,100	
HLRS 2030-03-200				20				60	6	9,100	
HLRS 2030-03-260				26				70	6	9,100	
HLRS 2030-03-300				30				70	6	9,100	
HLRS 2030-03-360				36				80	6	11,200	
HLRS 2030-05-060				RO.5				6	55	6	6,000
HLRS 2030-05-060E	○							6	55	6	6,600
HLRS 2030-05-120			12					55	6	7,800	
HLRS 2030-05-160			16					60	6	9,100	
HLRS 2030-05-160E	○		16					60	6	10,010	
HLRS 2030-05-180			18					60	6	9,100	
HLRS 2030-05-200		20	60		6	9,100					
HLRS 2030-05-260		26	70		6	9,100					
HLRS 2030-05-300		30	70		6	9,100					
HLRS 2030-05-360		36	80		6	11,200					

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Next Page →

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_1$	Effective Length by Inclined Angles					
					30'	1°	1°30'	2°	3°	
HLRS 2030-01-060		3	R0.1	6	6.21	6.42	6.63	6.86	7.37	
HLRS 2030-01-060E	○			6	6.21	6.42	6.63	6.86	7.37	
HLRS 2030-01-120				12	12.40	12.81	13.23	13.69	14.72	
HLRS 2030-01-160				16	16.53	17.06	17.64	18.25	19.61	
HLRS 2030-01-160E	○			16	16.53	17.06	17.64	18.25	19.61	
HLRS 2030-01-180				18	18.59	19.19	19.84	20.53	22.06	
HLRS 2030-01-200				20	20.65	21.32	22.04	22.80	24.51	
HLRS 2030-01-260				26	26.84	27.71	28.64	29.64	No Interference	
HLRS 2030-01-300				30	30.97	31.97	33.04	34.19	No Interference	
HLRS 2030-01-360				36	37.16	38.36	39.65	41.02	No Interference	
HLRS 2030-02-060				R0.2	6	6.21	6.41	6.63	6.85	7.36
HLRS 2030-02-060E	○				6	6.21	6.41	6.63	6.85	7.36
HLRS 2030-02-120			12		12.40	12.80	13.23	13.69	14.71	
HLRS 2030-02-160			16		16.53	17.06	17.63	18.24	19.60	
HLRS 2030-02-160E	○		16		16.53	17.06	17.63	18.24	19.60	
HLRS 2030-02-180			18		18.59	19.19	19.83	20.52	22.05	
HLRS 2030-02-200			20		20.65	21.32	22.03	22.80	24.49	
HLRS 2030-02-260			26		26.84	27.71	28.64	29.63	No Interference	
HLRS 2030-02-300			30		30.97	31.97	33.04	34.18	No Interference	
HLRS 2030-02-360			36		37.15	38.36	39.64	41.02	No Interference	
HLRS 2030-03-060			R0.3		6	6.21	6.41	6.62	6.85	7.35
HLRS 2030-03-060E	○				6	6.21	6.41	6.62	6.85	7.35
HLRS 2030-03-120				12	12.40	12.80	13.22	13.68	14.70	
HLRS 2030-03-160				16	16.53	17.06	17.63	18.23	19.59	
HLRS 2030-03-160E	○			16	16.53	17.06	17.63	18.23	19.59	
HLRS 2030-03-180				18	18.59	19.19	19.83	20.51	22.04	
HLRS 2030-03-200				20	20.65	21.32	22.03	22.79	24.48	
HLRS 2030-03-260				26	26.84	27.71	28.63	29.62	No Interference	
HLRS 2030-03-300				30	30.96	31.97	33.03	34.18	No Interference	
HLRS 2030-03-360				36	37.15	38.35	39.64	41.01	No Interference	
HLRS 2030-05-060				R0.5	6	6.21	6.40	6.61	6.83	7.33
HLRS 2030-05-060E	○				6	6.21	6.40	6.61	6.83	7.33
HLRS 2030-05-120			12		12.40	12.79	13.21	13.67	14.67	
HLRS 2030-05-160			16		16.52	17.05	17.62	18.22	19.57	
HLRS 2030-05-160E	○		16		16.52	17.05	17.62	18.22	19.57	
HLRS 2030-05-180			18		18.58	19.18	19.82	20.50	22.02	
HLRS 2030-05-200		20	20.65		21.31	22.02	22.78	24.46		
HLRS 2030-05-260		26	26.84		27.70	28.62	29.61	No Interference		
HLRS 2030-05-300		30	30.96		31.96	33.02	34.16	No Interference		
HLRS 2030-05-360		36	37.15		38.35	39.63	41.00	No Interference		



Next Page ➔

## 2 Flutes HARDMAX

Unit (mm)


Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_e$	Length of Cut $\ell$	Neck Diameter $\phi d_i$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥
HLRS 2030-10-060		3	R1	6	3	2.92	16°	55	6	6,000
HLRS 2030-10-060E	○			6				6,600		
HLRS 2030-10-120				12				7,800		
HLRS 2030-10-160				16				9,100		
HLRS 2030-10-160E	○			16				10,010		
HLRS 2030-10-180				18				9,100		
HLRS 2030-10-200				20				9,100		
HLRS 2030-10-260				26				9,100		
HLRS 2030-10-300				30				9,100		
HLRS 2030-10-360				36				11,200		
HLRS 2040-01-080		4	RO.1	8	4	3.82	16°	65	6	7,800
HLRS 2040-01-080E	○			8				8,580		
HLRS 2040-01-120				12				8,000		
HLRS 2040-01-160				16				9,400		
HLRS 2040-01-200				20				10,130		
HLRS 2040-01-200E	○			20				11,140		
HLRS 2040-01-240				24				10,130		
HLRS 2040-01-320				32				10,130		
HLRS 2040-01-480			48	16,200						
HLRS 2040-02-080			RO.2	8				65	6	7,800
HLRS 2040-02-080E	○			8				65	6	8,580
HLRS 2040-02-120				12				65	6	8,000
HLRS 2040-02-160				16				65	6	9,400
HLRS 2040-02-200				20				65	6	10,130
HLRS 2040-02-200E	○			20				65	6	11,140
HLRS 2040-02-240				24				70	6	10,130
HLRS 2040-02-320				32				80	6	10,130
HLRS 2040-02-480			48	100				6	16,200	
HLRS 2040-03-080			RO.3	8				65	6	7,800
HLRS 2040-03-080E	○			8				65	6	8,580
HLRS 2040-03-120		12		65	6	8,000				
HLRS 2040-03-160		16		65	6	9,400				
HLRS 2040-03-200		20		65	6	10,130				
HLRS 2040-03-200E	○	20		65	6	11,140				
HLRS 2040-03-240		24		70	6	10,130				
HLRS 2040-03-320		32		80	6	10,130				
HLRS 2040-03-480		48	100	6	16,200					
HLRS 2040-05-080		RO.5	8	65	6	7,800				
HLRS 2040-05-080E	○		8	65	6	8,580				
HLRS 2040-05-120			12	65	6	8,000				
HLRS 2040-05-160			16	65	6	9,400				
HLRS 2040-05-200			20	65	6	10,130				
HLRS 2040-05-200E	○		20	65	6	11,140				
HLRS 2040-05-240			24	70	6	10,130				
HLRS 2040-05-320			32	80	6	10,130				
HLRS 2040-05-480		48	100	6	16,200					

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Next Page →

Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_e$	Effective Length by Inclined Angles				
					30'	1°	1°30'	2°	3°
HLRS 2030-10-060		3	R1	6	6.20	6.39	6.59	6.80	7.28
HLRS 2030-10-060E	○			6	6.20	6.39	6.59	6.80	7.28
HLRS 2030-10-120				12	12.39	12.78	13.19	13.63	14.62
HLRS 2030-10-160				16	16.51	17.04	17.59	18.19	19.52
HLRS 2030-10-160E	○			16	16.51	17.04	17.59	18.19	19.52
HLRS 2030-10-180				18	18.58	19.17	19.79	20.47	21.96
HLRS 2030-10-200				20	20.64	21.29	21.99	22.74	24.41
HLRS 2030-10-260				26	26.83	27.68	28.60	29.57	No Interference
HLRS 2030-10-300				30	30.95	31.94	33.00	34.13	No Interference
HLRS 2030-10-360				36	37.14	38.33	39.60	40.96	No Interference
HLRS 2040-01-080		4	RO.1	8	8.45	8.73	9.02	9.33	10.03
HLRS 2040-01-080E	○			8	8.45	8.73	9.02	9.33	10.03
HLRS 2040-01-120				12	12.58	12.99	13.42	13.89	14.92
HLRS 2040-01-160				16	16.70	17.25	17.82	18.44	No Interference
HLRS 2040-01-200				20	20.83	21.50	22.23	23.00	No Interference
HLRS 2040-01-200E	○			20	20.83	21.50	22.23	23.00	No Interference
HLRS 2040-01-240				24	24.95	25.76	26.63	27.55	No Interference
HLRS 2040-01-320				32	33.21	34.28	35.43	No Interference	No Interference
HLRS 2040-01-480			48	49.71	51.32	No Interference	No Interference	No Interference	
HLRS 2040-02-080			RO.2	8	8.45	8.72	9.01	9.33	10.02
HLRS 2040-02-080E	○			8	8.45	8.72	9.01	9.33	10.02
HLRS 2040-02-120				12	12.58	12.98	13.42	13.88	14.91
HLRS 2040-02-160				16	16.70	17.24	17.82	18.44	No Interference
HLRS 2040-02-200				20	20.83	21.50	22.22	22.99	No Interference
HLRS 2040-02-200E	○			20	20.83	21.50	22.22	22.99	No Interference
HLRS 2040-02-240				24	24.95	25.76	26.62	27.54	No Interference
HLRS 2040-02-320				32	33.20	34.28	35.43	No Interference	No Interference
HLRS 2040-02-480				48	49.71	51.32	No Interference	No Interference	No Interference
HLRS 2040-03-080				RO.3	8	8.45	8.72	9.01	9.32
HLRS 2040-03-080E	○		8		8.45	8.72	9.01	9.32	10.01
HLRS 2040-03-120			12		12.58	12.98	13.41	13.87	14.69
HLRS 2040-03-160			16		16.70	17.24	17.81	18.43	No Interference
HLRS 2040-03-200			20		20.83	21.50	22.22	22.98	No Interference
HLRS 2040-03-200E	○		20		20.83	21.50	22.22	22.98	No Interference
HLRS 2040-03-240			24		24.95	25.76	26.62	27.54	No Interference
HLRS 2040-03-320			32		33.20	34.28	35.42	No Interference	No Interference
HLRS 2040-03-480			48		49.71	51.31	No Interference	No Interference	No Interference
HLRS 2040-05-080			RO.5		8	8.45	8.71	9.00	9.31
HLRS 2040-05-080E	○	8		8.45	8.71	9.00	9.31	9.99	
HLRS 2040-05-120		12		12.57	12.97	13.40	13.86	14.88	
HLRS 2040-05-160		16		16.70	17.23	17.80	18.42	No Interference	
HLRS 2040-05-200		20		20.82	21.49	22.21	22.97	No Interference	
HLRS 2040-05-200E	○	20		20.82	21.49	22.21	22.97	No Interference	
HLRS 2040-05-240		24		24.95	25.75	26.61	27.52	No Interference	
HLRS 2040-05-320		32		33.20	34.27	35.41	No Interference	No Interference	
HLRS 2040-05-480		48		49.70	51.31	No Interference	No Interference	No Interference	




Next Page ➡

## 2 Flutes HARDMAX

Unit (mm)


Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $\ell_1$	Length of Cut $\ell$	Neck Diameter $\phi d_1$	Shank Taper Angle Bta	Overall Length L	Shank Diameter $\phi d$	Suggested Retail Price ¥				
HLRS 2040-10-080		4	R1	8	4	3.82	16°	65	6	7,800				
HLRS 2040-10-080E	○			8				65	6	8,580				
HLRS 2040-10-120				12				65	6	8,000				
HLRS 2040-10-160				16				65	6	9,400				
HLRS 2040-10-200				20				65	6	10,130				
HLRS 2040-10-200E	○			20				65	6	11,140				
HLRS 2040-10-240				24				70	6	10,130				
HLRS 2040-10-320				32				80	6	10,130				
HLRS 2040-10-480				48				100	6	16,200				
HLRS 2050-02-200				5				RO.2	20	5	4.82	16°	70	6
HLRS 2050-02-400		40	90		6	16,200								
HLRS 2050-03-200		RO.3	20		70	6	12,900							
HLRS 2050-03-400			40		90	6	16,200							
HLRS 2050-05-200		RO.5	20		70	6	12,900							
HLRS 2050-05-400			40		90	6	16,200							
HLRS 2050-10-200		R1	20		70	6	12,900							
HLRS 2050-10-400			40		90	6	16,200							
HLRS 2060-01-120		6	RO.1		12	6	5.82	-	65				6	12,900
HLRS 2060-01-120E	○				12				65				6	14,190
HLRS 2060-01-200				20	70				6	12,900				
HLRS 2060-01-300				30	100				6	16,700				
HLRS 2060-01-300E	○			30	100				6	18,370				
HLRS 2060-01-600			60	120	6				20,300					
HLRS 2060-02-120			RO.2	12	65				6	12,900				
HLRS 2060-02-120E	○			12	65				6	14,190				
HLRS 2060-02-200				20	70				6	12,900				
HLRS 2060-02-300				30	100				6	16,700				
HLRS 2060-02-300E	○	30		100	6	18,370								
HLRS 2060-02-600		60	120	6	20,300									
HLRS 2060-03-120		RO.3	12	65	6	12,900								
HLRS 2060-03-120E	○		12	65	6	14,190								
HLRS 2060-03-200			20	70	6	12,900								
HLRS 2060-03-300			30	100	6	16,700								
HLRS 2060-03-300E	○		30	100	6	18,370								
HLRS 2060-03-600		60	120	6	20,300									
HLRS 2060-05-120		RO.5	12	65	6	12,900								
HLRS 2060-05-120E	○		12	65	6	14,190								
HLRS 2060-05-200			20	70	6	12,900								
HLRS 2060-05-300			30	100	6	16,700								
HLRS 2060-05-300E	○		30	100	6	18,370								
HLRS 2060-05-600		60	120	6	20,300									
HLRS 2060-10-120		R1	12	65	6	12,900								
HLRS 2060-10-120E	○		12	65	6	14,190								
HLRS 2060-10-200			20	70	6	12,900								
HLRS 2060-10-300			30	100	6	16,700								
HLRS 2060-10-300E	○		30	100	6	18,370								
HLRS 2060-10-600		60	120	6	20,300									





Unit (mm)

Model Number	Excellent	Outside Diameter $\phi D$	Corner Radius CR	Effective Length $l_e$	Effective Length by Inclined Angles					
					30°	1°	1°30'	2°	3°	
HLRS 2040-10-080		4	R1	8	8.44	8.70	8.98	9.27	9.93	
HLRS 2040-10-080E	○			8	8.44	8.70	8.98	9.27	9.93	
HLRS 2040-10-120				12	12.56	12.96	13.38	13.83	14.83	
HLRS 2040-10-160				16	16.69	17.22	17.78	18.38	19.72	
HLRS 2040-10-200				20	20.82	21.48	22.18	22.94	No Interference	
HLRS 2040-10-200E	○			20	20.82	21.48	22.18	22.94	No Interference	
HLRS 2040-10-240				24	24.94	25.74	26.58	27.49	No Interference	
HLRS 2040-10-320				32	33.19	34.25	35.39	No Interference	No Interference	
HLRS 2040-10-480				48	49.69	51.29	No Interference	No Interference	No Interference	
HLRS 2050-02-200				5	R0.2	20	20.83	21.50	No Interference	No Interference
HLRS 2050-02-400		40	41.46			No Interference	No Interference	No Interference	No Interference	
HLRS 2050-03-200		R0.3	20		20.83	21.50	No Interference	No Interference	No Interference	
HLRS 2050-03-400			40		41.45	No Interference	No Interference	No Interference	No Interference	
HLRS 2050-05-200		R0.5	20		20.82	21.49	No Interference	No Interference	No Interference	
HLRS 2050-05-400			40		41.45	No Interference	No Interference	No Interference	No Interference	
HLRS 2050-10-200		R1	20		20.82	21.48	No Interference	No Interference	No Interference	
HLRS 2050-10-400			40		41.44	No Interference	No Interference	No Interference	No Interference	
HLRS 2060-01-120		6	R0.1		12	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-01-120E	○				12	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-01-200				20	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-01-300				30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-01-300E	○			30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-01-600				60	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-120			R0.2	12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-120E	○			12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-200				20	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-300				30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-300E	○			30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-02-600				60	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-120			R0.3	12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-120E	○			12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-200				20	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-300				30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-300E	○			30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-03-600				60	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-120			R0.5	12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-120E	○			12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-200				20	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-300				30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-300E	○			30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-05-600				60	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-120			R1	12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-120E	○			12	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-200				20	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-300				30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-300E	○			30	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference
HLRS 2060-10-600				60	No Interference	No Interference	No Interference	No Interference	No Interference	No Interference



Milling Conditions for HLRS (2 Flutes)

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

WORK MATERIAL			Copper OFC / TPC				PREHARDENED STEELS HARDENED STEELS NAK / SKD (30~45HRC)				HARDENED STEELS SKD / SKT (45~55HRC)				HARDENED STEELS SKD / SKH (55~65HRC)			
Model Number	Outside Diameter (mm)	Effective Length (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)
2002	0.2	0.5	55,000	230	0.027	0.02	55,000	230	0.006	0.02	44,800	236	0.005	0.02	19,000	30	0.002	0.015
		1	55,000	200	0.027	0.02	55,000	200	0.006	0.02	35,000	150	0.004	0.02	15,000	25	0.0015	0.015
		1.5	55,000	180	0.017	0.01	55,000	180	0.005	0.01	27,000	100	0.003	0.01	12,000	20	0.001	0.007
		2	55,000	170	0.007	0.005	55,000	170	0.003	0.005	20,000	60	0.002	0.005	10,500	15	0.001	0.003
2003	0.3	1	60,000	500	0.03	0.02	60,000	500	0.007	0.02	35,000	350	0.005	0.02	22,000	35	0.004	0.015
		1.5	60,000	470	0.03	0.02	60,000	470	0.007	0.02	35,000	310	0.005	0.018	22,000	33	0.004	0.015
		2	60,000	400	0.03	0.02	60,000	400	0.007	0.02	33,200	250	0.005	0.015	20,000	32	0.004	0.015
		2.5	57,000	330	0.03	0.017	57,000	330	0.007	0.017	30,000	180	0.003	0.012	18,000	30	0.002	0.012
		3	52,000	220	0.03	0.015	52,000	220	0.006	0.015	25,000	80	0.003	0.01	15,000	20	0.002	0.01
2004	0.4	1	50,900	610	0.048	0.063	50,900	510	0.013	0.072	40,700	370	0.011	0.072	24,200	40	0.004	0.072
		1.5	45,200	580	0.045	0.063	45,200	480	0.012	0.054	36,200	360	0.01	0.054	21,500	38	0.004	0.054
		2	40,400	540	0.042	0.054	40,400	450	0.011	0.045	32,300	330	0.009	0.045	19,200	35	0.004	0.045
		3	33,900	460	0.027	0.054	33,900	390	0.008	0.027	27,100	280	0.007	0.027	16,100	30	0.003	0.027
		4	30,000	220	0.01	0.045	30,000	340	0.006	0.014	24,000	250	0.005	0.014	14,300	27	0.002	0.014
2005	0.5	1	49,200	1,370	0.081	0.117	49,200	1,140	0.034	0.122	40,000	860	0.03	0.122	24,800	94	0.013	0.122
		2	39,900	1,000	0.075	0.108	39,900	830	0.029	0.117	32,500	630	0.026	0.117	20,100	68	0.011	0.117
		3	31,900	770	0.057	0.09	31,900	640	0.023	0.113	26,000	480	0.02	0.113	16,100	52	0.008	0.113
		4	29,100	660	0.039	0.072	29,100	550	0.016	0.108	23,700	410	0.014	0.108	14,600	45	0.006	0.108
		5	26,400	570	0.027	0.045	26,400	470	0.011	0.099	21,500	360	0.01	0.099	13,300	39	0.004	0.099
		6	24,200	480	0.021	0.018	24,200	400	0.007	0.09	19,700	300	0.006	0.09	12,200	33	0.003	0.09
2006	0.6	2	28,600	610	0.114	0.162	28,600	510	0.01	0.219	23,700	390	0.01	0.219	15,200	43	0.004	0.219
		3	23,800	480	0.09	0.135	23,800	400	0.008	0.108	19,700	300	0.007	0.108	12,600	33	0.003	0.108
		4	20,400	400	0.063	0.108	20,400	330	0.005	0.104	16,800	250	0.005	0.104	10,800	28	0.002	0.104
		6	16,800	300	0.036	0.045	16,800	250	0.003	0.099	13,900	190	0.003	0.099	8,900	21	0.001	0.099
		8	14,600	240	0.021	0.027	14,600	200	0.002	0.072	12,100	150	0.002	0.072	7,700	16	0.001	0.072
2007	0.7	4	18,400	480	0.087	0.162	18,400	400	0.008	0.117	15,500	310	0.008	0.117	10,200	35	0.004	0.117
		6	15,400	360	0.051	0.108	15,400	300	0.005	0.108	13,000	230	0.005	0.108	8,600	26	0.002	0.108
2008	0.8	4	17,500	540	0.132	0.198	17,500	450	0.014	0.117	15,000	360	0.015	0.117	10,200	41	0.007	0.117
		6	14,600	410	0.075	0.144	14,600	340	0.008	0.108	12,500	270	0.008	0.108	8,500	30	0.004	0.108
		8	12,800	310	0.03	0.1	12,800	270	0.005	0.09	11,000	185	0.004	0.09	7,600	20	0.002	0.09
2010	1	2	17,600	1,100	0.21	0.45	17,600	920	0.035	0.27	15,300	750	0.04	0.27	10,900	89	0.02	0.27
		3	15,500	1,050	0.205	0.425	15,500	870	0.031	0.27	13,200	720	0.037	0.27	9,400	86	0.018	0.27
		4	13,800	980	0.201	0.405	13,800	820	0.03	0.27	12,000	670	0.035	0.27	8,500	80	0.017	0.27
		5	12,500	900	0.16	0.4	12,500	720	0.025	0.24	11,000	600	0.03	0.24	7,800	72	0.015	0.24
		6	11,300	790	0.117	0.387	11,300	650	0.021	0.216	9,800	540	0.024	0.216	7,000	64	0.012	0.216
		8	9,800	590	0.072	0.36	9,800	490	0.016	0.189	8,500	400	0.018	0.189	6,100	48	0.009	0.189
		10	8,800	390	0.048	0.315	8,800	320	0.011	0.126	7,600	270	0.013	0.126	5,400	32	0.006	0.126
		12	8,100	260	0.033	0.27	8,100	210	0.008	0.072	7,000	180	0.009	0.072	5,000	21	0.004	0.072
		16	7,000	230	0.018	0.225	7,000	190	0.004	0.027	6,100	160	0.005	0.027	4,300	19	0.002	0.027
		20	6,300	160	0.015	0.18	6,300	130	0.003	0.018	5,500	110	0.003	0.018	3,900	13	0.001	0.018

## Milling Conditions for HLRS (2 Flutes)

WORK MATERIAL			Copper OFC / TPC				PREHARDENED STEELS HARDENED STEELS NAK / SKD (30~45HRC)				HARDENED STEELS SKD / SKT (45~55HRC)				HARDENED STEELS SKD / SKH (55~65HRC)			
Model Number	Outside Diameter (mm)	Effective Length (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)
2012	1.2	6	9,400	700	0.186	0.468	9,400	580	0.018	0.09	8,400	490	0.022	0.09	6,200	60	0.011	0.09
		12	6,800	440	0.054	0.405	6,800	370	0.007	0.072	6,100	310	0.008	0.072	4,500	38	0.004	0.072
		20	5,400	250	0.021	0.24	5,400	210	0.003	0.018	4,800	180	0.003	0.018	3,500	22	0.002	0.018
2015	1.5	4	13,200	1,310	0.3	0.675	13,200	1,090	0.045	0.45	12,000	950	0.06	0.45	9,200	124	0.033	0.45
		6	10,600	1,240	0.282	0.63	10,600	1,030	0.041	0.405	9,700	900	0.055	0.405	7,400	117	0.03	0.405
		8	9,300	1,050	0.204	0.612	9,300	870	0.034	0.315	8,500	760	0.045	0.315	6,500	99	0.025	0.315
		10	8,500	900	0.15	0.567	8,500	750	0.032	0.288	7,800	650	0.042	0.288	6,000	85	0.023	0.288
		12	7,800	800	0.114	0.54	7,800	670	0.029	0.27	7,100	580	0.038	0.27	5,400	76	0.021	0.27
		16	6,800	620	0.066	0.45	6,800	510	0.015	0.18	6,200	450	0.02	0.18	4,700	58	0.011	0.18
		20	6,000	490	0.042	0.36	6,000	410	0.005	0.108	5,500	360	0.006	0.108	4,200	46	0.003	0.108
2020	2	4	15,300	1,500	0.33	0.9	15,300	1,250	0.046	0.9	14,300	1,130	0.065	0.9	11,500	162	0.039	0.9
		6	12,800	1,220	0.321	0.855	12,800	1,020	0.043	0.81	12,000	930	0.06	0.81	9,700	133	0.036	0.81
		8	11,200	1,120	0.267	0.81	11,200	930	0.039	0.72	10,400	850	0.055	0.72	8,400	121	0.033	0.72
		10	10,000	1,050	0.225	0.765	10,000	870	0.033	0.585	9,300	790	0.047	0.585	7,600	113	0.028	0.585
		12	9,100	980	0.186	0.72	9,100	820	0.031	0.45	8,500	740	0.044	0.45	6,900	107	0.026	0.45
		16	7,800	830	0.132	0.702	7,800	690	0.028	0.315	7,300	630	0.039	0.315	5,900	90	0.023	0.315
		20	7,000	770	0.093	0.666	7,000	640	0.017	0.198	6,600	580	0.024	0.198	5,300	84	0.014	0.198
		26	6,200	700	0.06	0.54	6,200	580	0.006	0.144	5,800	530	0.008	0.144	4,600	75	0.005	0.144
		30	6,000	670	0.05	0.45	6,000	550	0.005	0.135	5,500	500	0.005	0.135	4,400	70	0.002	0.135
2025	2.5	10	10,500	1,220	0.339	0.855	10,500	1,020	0.052	0.54	10,000	960	0.075	0.54	8,400	154	0.048	0.54
		20	7,800	720	0.165	0.756	7,800	600	0.024	0.225	7,500	560	0.035	0.225	6,300	91	0.022	0.225
		30	6,300	540	0.069	0.63	6,300	450	0.011	0.18	6,000	420	0.016	0.18	5,000	67	0.01	0.18
2030	3	6	14,000	2,700	0.5	0.9	14,000	1,510	0.15	0.72	13,300	1,140	0.15	0.72	12,000	270	0.1	0.72
		12	10,500	1,600	0.39	0.85	10,500	1,150	0.105	0.67	10,000	890	0.105	0.67	9,000	200	0.075	0.67
		16	9,200	1,160	0.321	0.81	9,200	960	0.081	0.63	8,800	730	0.081	0.63	7,900	173	0.054	0.63
		18	8,800	1,100	0.29	0.79	8,800	900	0.078	0.6	8,300	700	0.078	0.6	7,500	160	0.048	0.6
		20	8,400	1,050	0.26	0.78	8,400	880	0.073	0.58	7,900	680	0.073	0.58	7,100	150	0.044	0.58
		26	7,500	980	0.18	0.72	7,500	820	0.065	0.495	7,100	620	0.065	0.495	6,400	146	0.043	0.495
		30	7,000	870	0.14	0.69	7,000	720	0.05	0.38	6,500	560	0.05	0.38	6,000	118	0.029	0.38
		36	6,400	710	0.09	0.63	6,400	590	0.022	0.18	6,100	440	0.022	0.18	5,500	105	0.014	0.18
2040	4	8	10,200	1,340	0.42	1.62	10,200	1,110	0.095	1.35	8,500	970	0.14	1.35	7,300	223	0.101	1.35
		12	8,900	1,300	0.41	1.56	8,900	1,080	0.083	1.15	7,600	950	0.12	1.15	6,400	215	0.085	1.15
		16	7,900	1,250	0.4	1.5	7,900	1,030	0.065	1	6,600	910	0.1	1	5,600	205	0.065	1
		20	6,900	1,190	0.384	1.44	6,900	990	0.054	0.9	5,800	860	0.08	0.9	4,900	198	0.058	0.9
		24	6,200	1,100	0.31	1.38	6,200	900	0.043	0.8	5,200	770	0.065	0.8	4,500	175	0.043	0.8
		32	5,500	860	0.189	1.26	5,500	720	0.027	0.648	4,600	630	0.04	0.648	3,900	144	0.029	0.648
		48	4,600	430	0.093	1.08	4,600	360	0.007	0.315	3,900	310	0.01	0.315	3,300	72	0.007	0.315



3mm Shank  
V Series



UDC-PCD  
Series



CBN  
Series



Square



Long Neck  
Square



Radius



Long Neck  
Radius



Taper Neck  
Radius



Ball / Long  
Shank Ball



Long Neck  
Ball



Taper Neck  
Ball



Taper



Barrel



Spiral  
V Cutter



Drill




Technical Data

Milling Conditions for HLRS (2 Flutes)

WORK MATERIAL			Copper OFC / TPC				PREHARDENED STEELS HARDENED STEELS NAK / SKD (30~45HRC)				HARDENED STEELS SKD / SKT (45~55HRC)				HARDENED STEELS SKD / SKH (55~65HRC)			
Model Number	Outside Diameter (mm)	Effective Length (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)	Spindle Speed (min <sup>-1</sup> )	Feed Rate (mm/min)	a <sub>p</sub> Axial Depth (mm)	a <sub>e</sub> Radial Depth (mm)
2050	5	20	6,700	1,780	0.606	1.98	6,700	1,480	0.092	1.17	4,800	990	0.13	1.17	4,000	297	0.096	1.17
		40	4,600	850	0.297	1.53	4,600	710	0.046	0.9	3,300	470	0.065	0.9	2,800	143	0.048	0.9
2060	6	12	8,000	1,800	0.6	2.25	8,000	1,620	0.5	1.35	4,700	1,360	0.2	1.35	4,000	540	0.15	1.35
		20	5,800	1,350	0.58	2.12	5,800	1,180	0.46	1.31	3,500	1,000	0.18	1.31	3,000	380	0.14	1.31
		30	4,500	1,060	0.546	1.98	4,500	880	0.396	1.26	2,600	740	0.158	1.26	2,200	294	0.119	1.26
		60	2,800	530	0.156	1.62	2,800	440	0.113	0.99	1,600	370	0.045	0.99	1,400	147	0.034	0.99

- φ3mm Shank V Series
- UDC-PCD Series
- CBN Series
- Square
- Long Neck Square
- Radius
- Long Neck Radius
- Taper Neck Radius
- Ball / Long Shank Ball
- Long Neck Ball
- Taper Neck Ball
- Taper
- Barrel
- Spiral V Cutter
- Drill
- Technical Data

Side Milling



Note:

- Decrease both spindle speed and feed rate proportionally when the milling parameters exceed the machine's maximum spindle speed.
- Every coolant offers stable milling.
- Recommend oil coolant for Stainless Steels and Heat Resistant Alloys.
- Recommend wet coolant for Copper.



	Ø3mm Shank V Series
	UDC-PCD Series
	CBN Series
Square	Square
	Long Neck Square
Radius	Radius
	<b>Long Neck Radius</b>
	Taper Neck Radius
Ball	Ball / Long Shank Ball
	Long Neck Ball
	Taper Neck Ball
Taper	Taper
	Barrel
	Spiral V Cutter
	Drill
	Technical Data